

++____


HENAN KINGCLIMA INDUSTRY CO.,LTD ADD:A2301 SHENGHUI CENTRE,16 NONGYE RD(450000), Zhengzhou,China


TEL: +86-371-66379266 +86-371-66379166 http://www.kingclima.com Email: info@kingclima.com


Unique Features of CoolPro3000 Parking Truck Air Conditioners


- Extra-slim and compact design of Height 20cm.
- Matched with truck sunroof size and do not to slotting in cabins , Suitable for sunroof size from 400x400mm to 900x600mm.
- Full electric system. There is no need to start the engine to provide power when parking, unloading the cargo, driver rests.
- Very low power consumption min 300W, with ECO mode to save electricity .
- The maximum cooling capacity of 3,000w /10,350BTU ,Use brushless motor and internal compressor design suspension pillar shock absorption, Very low noise less than 45 db give you a comfortable sleeping environment!
- Injection mold, anti-aging, no deformation, air conditioning internal insulation layer is made of environmentally friendly materials and flame retardant, green travel!

With voltage protection function, the battery voltage is automatically disconnected when the battery voltage is low to the minimum starting voltage of the vehicle. There is no need to worry about starting the startup problem and protect the battery life.














		CoolPro3000 Technical Data / Parameters
Dimensions		1040*755*180
Air Volume		450m³/h
Cut size/Skylight size		400*400mm or 600*300mm
Weight		35KG
Time of endurance		10 hours (Intelligent frequency control)
Control mode		PWM
Power		300-700W
Rated Current		50/60A
Refrigerant		R134a600g
Rated Cooling Capacity		3000W/10350 BTU
Core component	Circulating air volume	450M3/H
	Energy efficiency ratio	1.5-2.6W/W
	Condenser	Parallel flow,Double fin,Dimensions:53*34*2 cm
	Evaporator fan	Tupe belt type、Dimension: 41*13*6 cm
	Voltage	DC24V/DC12V









